

Model	65IN	86IN	8IN
Display			
Active Screen Size	65"	86"	98"
Backlight	LED	LED	LED
Display Ratio	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Brightness	250-500cd/m ²	250-500 cd/m ²	500 cd/m ²
Dynamic Contrast	4000:1	4000:1	4000:1
Response Time	8ms	8ms	8ms
Viewing Angle	178°	178°	178°
Lifetime Hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours
Continuous Run Time	24/7	24/7	24/7
Power			
Max Power Consumption	≤200W	≤450W	≤700W
Speakers			
Max Power Output	10W X 2 (20W)	10W X 2 (20W)	10W X 2 (20W)
Transportation/Storage			
Storage Humidity	20~90%RH (non-condensing)	20~90%RH (non-condensing)	20~90%RH (non-condensing)
Working Humidity	20~80%RH (non-condensing)	20~80%RH (non-condensing)	20~80%RH (non-condensing)
Installation Method	Wall-mounted or Mobile Stand	Wall-mounted or Mobile Stand	Wall-mounted or Mobile Stand
VESA Mount Pattern	600x400mm	800x400mm	800x600mm
Net Weight (lbs)	62	113	190