

**GENIUS**
LET'S RISE...

Wall/Surface Mount Speaker

IT-774H/IT-775H/IT-776H/IT-778H



Description:

Indoor high-grade 2 -way wall/surface mounted speakers, multi-power fixed resistance and fixed pressure selection, modern sense of arc design, 2 frequency division design, high cost performance, convenient installation. Suitable for hotels, conference room, boardroom, training room, auditorium equipped with ABS enclosure.

Specifications:

Model	IT-774H	IT-775H	IT-776H	IT-778H
Power taps @100V/70V	2.5W, 5W, 10W, 20W	3.75W, 7.5W, 15W, 30W 1.9W	10W, 15W, 20W, 40W, 80W	10W, 15W, 20W, 40W, 80W
Total Power	250W Peak	300W Peak	320W Peak	400W Peak
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
Sensitivity	92dB	92dB	92dB	92dB
Max. SPL(1W/1M)	124dB	124dB	124dB	124dB
Frequency response (-10dB)	65-20KHz	65-20KHz	65-20KHz	65-20KHz
Speaker driver	4" x 1 1.5" x 1	5" x 1 1.5" x 1	6" x 1 0.25mm x 1	8" x 1 1.5" x 1
Nominal Dispersion	90°(H) × 90°(V)	90°(H) × 90°(V)	90°(H) × 90°(V)	90°(H) × 90°(V)
Weight	2.3kg	2.7kg	4.1kg	6.5kg
Protection level	IP65	IP65	IP65	IP65